



# SMART AND COMPATIBLE

## 4 inch Barcode Label Printer SLP-TX400

The SLP-TX400 is BIXOLON's thermal transfer/direct thermal label printer for 4 inch wide printing. This high-quality label printer features fast print speed up to 7 ips (178 mm/sec) and high compatibility based on perfect emulation support. The SLP-TX400 has Smart Media Detection function which automatically recognizes various types of labels when loading labels.




### HIGHLIGHTS

#### Powerful Printing Performance

- Paper feeding speed up to 7 ips (178 mm/sec)
- Thermal Transfer, Direct Thermal supported
- Fast data processing speed of various types of label

#### Smart Media Detection™

- Automatic paper detection such as gap media, black mark media and short length media paper



**BIXOLON**<sup>®</sup>  
a Better Solution for your Business™

# 4 inch Barcode Label Printer

## SLP-TX400



### FEATURES

#### All-in-one Interface

- Standard  
USB + Serial + Parallel
- Optional  
USB + Serial + Ethernet + WLAN\*



#### User-Friendly Options

- Easy installation Auto-Cutter
- Real-Time clock



Auto-Cutter : Easy installation

#### Powerful Compatibility

The SLP-TX400 is fully compatible with market-leading programming language; SLCS, BPL-Z™, BPL-E™.



BPL-Z™

BPL-E™

#### Label Artist™

Bixolon provides its custom label design program as bundle. It supports **database** connection as well as text, drawing lines and boxes, all kinds of graphics and 1D/2D Barcode printing.

BR-SLP-TX400-EN-MAR14

Copyright © BIXOLON Co., Ltd. All rights reserved.  
Features and specifications are subject to change without prior notice.

### SPECIFICATIONS

#### PRINT CHARACTERISTICS

**Printing Method:** Thermal Transfer, Direct Thermal  
**Printing Speed:** SLP-TX400: Up to 7 ips (178 mm/s) / SLP-TX403: Up to 5 ips (127 mm/s)  
**Print Resolution:** SLP-TX400: 203 dpi / SLP-TX403: 300 dpi  
**Printing Width:** SLP-TX400: Up to 108 mm / SLP-TX403: Up to 105.7 mm  
**Printing Length:** 6 ~ 1,000mm  
**Media Sensor:** Transmissive, Reflective (adjustable), Ribbon-End, Head open

#### MEDIA CHARACTERISTICS

**Media Type:** Gap, Black Mark, Notch, Continuous, Fan-Fold  
**Media Width:** 25 ~ 116 mm  
**Media Roll Diameter:** Up to 130 mm  
**Media Thickness:** 0.06 ~ 0.20 mm  
**Supply Method:** Easy Paper Loading

#### RIBBON CHARACTERISTICS

**Ribbon Type:** Wax, Wax / Resin, Resin, Outside  
**Ribbon Width:** 33 ~ 110 mm  
**Ribbon Length:** Up to 300 m  
**Core Inner Diameter:** 25.4 mm, 12.5 mm (optional)

#### PHYSICAL CHARACTERISTICS

**Dimensions (W x L x H):** 214 x 310 x 195 mm (8.42 x 12.20 x 7.67 inch)  
**Weight:** 2.85 kg (6.28 lbs.)

**Power:** EnergyStar Certified, External Power Adaptor 100-240V AC, 50/60Hz

#### PERFORMANCE CHARACTERISTICS

**Memory:** 64MB SDRAM, 128MB FlashROM  
**Interface:** Triple Interface  
 Standard: USB V2.0 HS + Serial + Parallel  
 Optional: USB V2.0 HS + Serial + Ethernet + WLAN\*  
 \* WLAN: 802.11b/g/n USB dongle type (optional)

#### ENVIRONMENT CHARACTERISTICS

**Temperature:** Operating: 5 ~ 40 °C (41 ~ 104 °F) / Storage: -20 ~ 60 °C (-4 ~ 140 °F)  
**Humidity:** Operating: 10 ~ 80% RH / Storage: 10 ~ 90% RH

#### SOFTWARE

**Emulation:** SLCS, BPL-Z™, BPL-E™  
**Driver / Utility:** Windows Driver (Euro Plus/Seagull), Linux CUPS Driver, Mac Driver, Virtual COM USB/Ethernet Driver, Utility Program, Label Artist™

**SDK:** Android SDK

#### FONTS / GRAPHICS / SYMBOLOGIES

**Fonts:** - 10 SLCS Resident Bitmap Fonts  
 - One SLCS Resident Scalable Font  
 - 16 BPL-Z™ Resident Bitmap Fonts  
 - One BPL-Z™ Resident Scalable Font  
 - 5 BPL-E™ Resident Bitmap Fonts  
 - 23 Code Page  
 - Unicode supported (UTF-8, UTF-16LE, UTF-16BE)

**Graphics:** Supporting user-defined fonts, graphics, formats, and logos

**Barcode Symbologies:** 1D: Codabar, Code 11, Code 39, Code 93, Code 128, EAN-13, EAN-8, Industrial 2-of-5, Interleaved 2-of-5, Logmars, MSI, Plessey, Postnet, GS1 DataBar (RSS-14), Standard 2-of-5, UPC/EAN extensions, UPC-A, UPC-E, IMB  
 2D: Aztec, Codablock, Code49, Data Matrix, MaxiCode, MicroPDF417, PDF417, QR Code, TLC39

#### OPTIONS

Ethernet, WLAN (USB dongle type), Peeler, Auto Cutter, RTC (Real Time Clock), External Paper Supply

**BIXOLON®**

www.bixolon.com



**BIXOLON Co., Ltd.**

7~8F, (Sampyeong-dong), 20, Pangyoyeok-ro241beon-gil,  
Bundang-gu, Seongnam-si, Gyeonggi-do, 463-400, Korea (ROK)

Tel +82 (0) 31 218 5500

Fax +82 (0) 31 218 5589

E-mail sales@bixolon.com

**BIXOLON America Inc.**

3171 Fujita St Torrance,  
CA 90505, USA

Tel +1 858 764 4580

Fax +1 310 257 6869

E-mail sales@bixolonusa.com

**BIXOLON Europe GmbH**

Tiefenbroicher Weg 35,  
40472 Düsseldorf, Germany

Tel +49 211 68 78 54 0

Fax +49 211 68 78 54 20

E-mail sales@bixolon.de