


COMPACT, DURABLE, AND PREMIUM



4 inch Thermal Transfer Desktop Label Printer **SLP-TX420**



HIGHLIGHTS




Flexible to Use

- Compatible with Android-based smart devices
- Triple interface supported: USB + Serial + Parallel
- Optional Ethernet and WLAN supported (USB dongle type)



Outstanding Form Factor

- Fast printing speed up to 7 ips (178 mm/sec)
- Quick data processing through powerful memory
- Compact design for 74 m ribbon
- Energy-efficient product



Intelligent Function

- Smart Media Detection™ is Bixolon's world-class technology that detects label length and media types such as gap media, black mark media, and short length media paper.
- Intelligent Leap-over™ detects empty label and automatically leaps to the next label.



BIXOLON[®]
a Better Solution for your Business™

4 inch Thermal Transfer Barcode Label Printer

SLP-TX420



Standard

Auto-cutter

Peeler

Premium-level Compatibility

Fully compatible with market-leading programming languages



BPL-Z™

BPL-E™

User-friendly Design

- Various type of media sensor supported
- Easy paper loading with adjustable paper guide
- Simple to change ribbon, thermal print head, and roller



Label Artist™

Bixolon provides its custom label design program as bundle. It supports **database** connection as well as text, drawing lines and boxes, all kinds of graphics and 1D/2D Barcode printing.

BR-SLP-TX420-EN-APR14

Copyright © BIXOLON Co., Ltd. All rights reserved.
Features and specifications are subject to change without prior notice.

SPECIFICATIONS

Printer Specifications

Print Method: Thermal Transfer, Direct Thermal
Print Speed: SLP-TX420: Up to 7 ips (178 mm/s) / SLP-TX423: Up to 5 ips (127 mm/s)
Print Resolution: SLP-TX420: 203 dpi / SLP-TX423: 300 dpi
Print Width: SLP-TX420: Up to 108 mm / SLP-TX423: Up to 105.7 mm
Print Length: 6 ~ 2000 mm
Sensor: Transmissive, Reflective (adjustable), Ribbon-End, Head open

Media Characteristics

Media Type: Gap, Black Mark, Notch, Continuous, Fan-Fold
Media Width: 20 ~ 110 mm
Media Roll Diameter: Up to 130 mm
Media Thickness: 0.06 ~ 0.20 mm
Supply Method: Easy Paper Loading

Ribbon Characteristics

Ribbon Type: Wax, Wax/Resin, Resin, Outside
Ribbon Width: 110 mm
Ribbon Length: Up to 74 m
Core Inner Diameter: 12.5 mm

Physical Characteristics

Dimensions (W x L x H): 200 x 252 x 173 mm (7.87 x 9.92 x 6.81 inch)
Weight: 2.35 kg (5.18 lbs.)

Power: EnergyStar Certified, External Power Adaptor 100-240V AC, 50/60Hz

Performance Characteristics

Memory: 64MB SDRAM, 128MB FlashROM

Interface: All-In-One Interface

Standard: USB V2.0 HS + Serial + Parallel



Optional: USB V2.0 HS + Serial + Ethernet + WLAN*



* WLAN: 802.11b/g/n USB dongle type (optional)

Environment Characteristics

Temperature: Operating: 5~40°C (41~104°F) / Storage: -20~60°C (-4~140°F)

Humidity: Operating: 10 ~ 80% RH / Storage 10 ~ 90% RH

Software

Emulation: SLCS, BPL-Z™, BPL-E™

Driver/Utility: Windows Driver (Euro Plus/Seagull), Linux CUPS Driver, Mac Driver, Virtual COM USB/Ethernet Driver, Utility Program, Label Artist™

SDK: Android SDK

Fonts / Graphics / Symbologies

Character Sets: · 10 SLCS Resident Bitmap Fonts

- One SLCS Resident Scalable Font
- 16 BPL-Z™ Resident Bitmap Fonts
- One BPL-Z™ Resident Scalable Font
- 5 BPL-E™ Resident Bitmap Fonts
- 23 Code Page
- Unicode supported (UTF-8, UTF-16LE, UTF-16BE)

Graphics: Supporting user-defined fonts, graphics, formats, and logos

Barcode Symbologies: 1D: Codabar, Code 11, Code 39, Code 93, Code 128, EAN-13, EAN-8, Industrial 2-of-5, Interleaved 2-of-5, Logmars, MSI, Plessey, Postnet, GS1 DataBar (RSS-14), Standard 2-of-5, UPC/EAN extensions, UPC-A, UPC-E, IMB
 2D: Aztec, Codablock, Code49, Data Matrix, MaxiCode, Micro-PDF417, PDF417, QR Code, TLC39

Options

Ethernet, WLAN (USB dongle type), Peeler, Auto Cutter, RTC (Real Time Clock), External Paper Supply

BIXOLON®

www.bixolon.com



BIXOLON Co., Ltd.

7~8F, (Sampyeong-dong), 20, Pangyoyeok-ro241beon-gil,
Bundang-gu, Seongnam-si, Gyeonggi-do, 463-400, Korea (ROK)

Tel +82 (0) 31 218 5500

Fax +82 (0) 31 218 5589

E-mail sales@bixolon.com

BIXOLON America Inc.

3171 Fujita St Torrance,
CA 90505, USA

Tel +1 858 764 4580

Fax +1 310 257 6869

E-mail sales@bixolonusa.com

BIXOLON Europe GmbH

Tiefenbroicher Weg 35,
40472 Düsseldorf, Germany

Tel +49 211 68 78 54 0

Fax +49 211 68 78 54 20

E-mail sales@bixolon.de