

# SRP-350III

3 inch POS printer



Retail



Hospitality



Ticketing



Kiosk

# The Industry's steady seller



### Powerful Printing Performance

- Fast printing up to 250mm/sec (25% faster than the SRP-350II)
- 4-type dithering options for graphic printing
- A family of the world-class SRP-350 line




### Multiple interface choice

- Built-in USB with a choice of Serial, Parallel, or Ethernet

### User-friendly Design

- Anti-jam guide
- Stand-alone or Space-saving wall-mount use
- 2" or 3" paper choice



# SRP-350III

## 3 inch POS printer

### Specifications

#### Print Characteristics

**Print Method**

Direct Thermal

**Print Speed**

SRP-350III: 250 mm/sec

SRP-352III: 230 mm/sec

**Print Resolution**

SRP-350III: 180 dpi

SRP-352III: 203 dpi

**Print Width**

Up to 72 mm

**Sensor**

Paper End, Paper Near End, Cover Open

#### Media Characteristics

**Media Type**

Receipt

**Media Width**

80 mm

Optional 58 mm (with 2 inch Partition)

**Media Roll Diameter**

Up to 83 mm

**Media Thickness**

0.062 ~ 0.075 mm

**Supply Method**

Easy Paper Loading

#### Physical Characteristics

**Dimensions (W x L x D)**

145 x 204 x 146 mm

(5.70 x 8.03 x 5.74 inch)

**Weight**

1.55kg (3.41 lbs)

**Power**

EnergyStar Certified,

External Power Adaptor 100-240V AV, 50/60Hz

**Drawer Port**

2 ports (via y-type adaptor)

#### Performance Characteristics

**Memory**

64 Mbit SDRAM, 32 Mbit FlashROM

**NV Image Memory**

256 Kbytes (mono)

**Receive Buffer**

4 Kbytes

**User Define Buffer**

12 Kbytes

**Interface**

Dual Interface

USB V2.0 FS + Serial

USB V2.0 FS + Parallel

USB V2.0 FS + Ethernet

#### Environment Characteristics

**Temperature**

Operating: 0 ~ 45°C (32 ~ 113°F)

Storage: -20 ~ 60°C (-4 ~ 140°F)

**Humidity**

Operating: 10 ~ 80% RH

Storage: 10 ~ 90% RH

#### Reliability

**Printer Unit (MCFB)**

70 Million Lines

**Thermal Print Head (TPH)**

150 km

**Auto Cutter**

1.8 Million Cuts

#### Software

**Emulation**

BXL / POS

**Driver / Utility**

Windows Driver, OPOS Driver, JPOS Driver,

Linux CUPS Driver, Mac Driver,

Virtual COM USB / Ethernet Driver, Utility Program

**SDK**

iOS SDK, Android SDK

#### Fonts / Graphics / Symbologies

**Character Size**

Font A: 12 x 24 Font B: 9 x 17 Font C: 9 x 24

KOR, CHN, JPN: 24 x 24

**Characters Per Line**

SRP-350III: Font A: 42 Font B, C: 56

KOR, CHN, JPN: 21

SRP-352III: Font A: 48 Font B, C: 64

KOR, CHN, JPN: 24

**Character Sets**

Alphanumeric: 95

Extended Graphics: 128 x 37 page

International: 32

**Graphics**

Supporting user-defined fonts, graphics, formats, and logos

**Barcode Symbologies**

1D: Codabar, Code 39, Code 93, Code 128,

EAN-8, EAN-13, ITF, UPC-A, UPC-E

2D: Data Matrix, PDF417, QR code

