

SRP-E770III

4 inch Direct Thermal



Logistics



Ticketing

Stadium
& Arenas

Warehousing





Healthcare



Retail

Economic and Compact



Basic Functions

- Printing speed up to 5 ips (127 mm/s)
- Fast data processing speed for various types of label
- The SRP-E770III is fully compatible with market-leading programming languages; SLCS, BPL-Z™, BPL-E™
- Smart switch programming language without setting the mode

User-Friendly Design

- Interface options:
 - SRP-E770III DUS : USB and Serial with Peeler
 - SRP-E770III DUE : USB and Ethernet with Peeler
- Compatible with label design software; BIXOLON's Label Artist™, Seagull's BarTender® and BarTender® UltraLite for BIXOLON

- Easy media loading with adjustable media width guide and folder
- Peeler as standard
- Various mode set ups via button confirmed by visual LED

SRP-E770III

4 inch Direct Thermal

Specifications

Printer Specifications

Print Method

Direct Thermal

Print Speed

Up to 5 ips (127 mm/sec)

Print Resolution

203 dpi

Print Width

Up to 104 mm

Print Length

Up to 1,000 mm

Sensor

Transmissive, Reflective, Head open

Media Characteristics

Media Type

Gap, Black Mark, Notch, Continuous, Fan-Fold

Media Width

42 ~ 106 mm

Media Roll Diameter

Up to 130 mm

Media Thickness

0.06 ~ 0.20 mm

Supply Method

Easy Paper Loading

Physical Characteristics

Dimensions (WxDxH)

189 x 221 x 171 mm

(7.44 x 8.70 x 6.73 inch)

Weight

1.47kg (3.24 lbs.)

Power

EnergyStar Certified,

External Power Adaptor 100-240V AC, 50/60Hz

Performance Characteristics

Memory

64 MB SDRAM, 128 MB Flash

Interface Options

i. SRP-E770III DUS : USB and Serial with Peeler

ii. SRP-E770III DUE : USB and Ethernet with Peeler

Environment Characteristics

Temperature

Operating: 0 ~ 40°C (32 ~ 104°F)

Storage: -20 ~ 60°C (-4 ~ 140°F)

Humidity

Operating: 10 ~ 80% RH

Storage: 10 ~ 90% RH

Software

Emulation

SLCS, BPL-Z™, BPL-E™

Driver / Utility

Windows Driver (Euro Plus/Seagull),
OPOS Driver, Linux / Mac CUPS Driver,
Virtual COM USB/Ethernet Driver,
Utility Program, Label Artist-II, Bartender UL

SDKs

iOS SDK, Android SDK, Windows SDK,
Linux SDK

Fonts / Graphics / Symbologies

Fonts

- 10 SLCS Resident Bitmap Fonts
- One SLCS Resident Scalable Font
- 16 BPL-Z™ Resident Bitmap Fonts
- One BPL-Z™ Resident Scalable Font
- 5 BPL-E™ Resident Bitmap Fonts
- 23 Code Page
- Unicode supported (UTF-8, UTF-16LE, UTF-16BE)

Graphics

Supporting user-defined fonts, graphics, formats, and logos

Barcode Symbologies

- 1D: Codabar, Code 11, Code 39, Code 93, Code 128, EAN-13, EAN-8, Industrial 2-of-5, Interleaved 2-of-5, Logmars, MSI, Plessey, Postnet, GS1 DataBar (RSS-14), Standard 2-of-5, UPC/EAN extensions, UPC-A, UPC-E, IMB
- 2D: Aztec, Codablock, Code49, Data Matrix, MaxiCode, MicroPDF417, PDF417, QR Code, TLC39



BR-SRP-E770III-EN-JUL18-BXE-V1

Copyright © BIXOLON Co., Ltd. All rights reserved. Features and specifications are subject to change without prior notice.

BIXOLON®

BIXOLON Co., Ltd.
+82 (0) 31 218 5500
sales@bixolon.com

BIXOLON America Inc.
+1 858 764 4580
sales@bixolonusa.com

BIXOLON Europe GmbH
+49 211 68 78 54 0
sales@bixolon.de

www.Bixolon.com

